

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**


**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A61M 25/01</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/62585</b> <b>(43) International Publication Date:</b> 9 December 1999 (09.12.99)
<b>(21) International Application Number:</b> PCT/US99/08409 <b>(22) International Filing Date:</b> 16 April 1999 (16.04.99)  <b>(30) Priority Data:</b> 09/087,482 29 May 1998 (29.05.98) US  <b>(71) Applicant:</b> MEDTRONIC, INC. [US/US]; 7000 Central Avenue N.E., Minneapolis, MN 55432 (US). <b>(72) Inventor:</b> BAUMANN, James, C.; 4709 Crofoot Avenue N.W., Buffalo, MN 55313 (US). <b>(74) Agents:</b> DUTHLER, Reed, A. et al.; Medtronic, Inc., 7000 Central Avenue N.E., MS301, Minneapolis, MN 55432 (US).		<b>(81) Designated States:</b> CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> METHOD AND APPARATUS FOR DEFLECTING A CATHETER OR LEAD    <b>(57) Abstract</b>  An apparatus for deflecting a catheter or lead, for example a deflectable stylet or guidewire. The device includes an outer tubular member, a tension member mounted within the outer tubular member and coupled to the outer member and a handle mounted at the proximal end of the tubular member. The handle includes a major handle portion which has a rotatable knob located at its distal end, surrounding a proximal portion of the outer tubular member and provided with inwardly directed threading and an inner slider member provided with outwardly directed threading engaging the inwardly directed threading of the knob. The slider is advanced or retracted longitudinally within the handle by rotation of the knob but is rotationally fixed with regard to the major handle portion. The outer tubular member is engaged at its proximal end with the inner slider member and the tension wire is fixedly engaged with the major handle portion, whereby rotation of the knob results in advancement or retraction of the outer tubular member relative to the tension wire and the major portion of the handle, which in turn causes the deflection of the outer tubular member.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**METHOD AND APPARATUS FOR DEFLECTING A CATHETER OR LEAD****Background of the Invention**

5 The present invention relates generally to implantable leads and catheters and more particularly to mechanisms for deflecting implantable leads and catheters to assist in guiding them through the vascular system.

10 Over the years, quite a number of mechanisms have been disclosed and employed to deflect catheters and implantable leads. These have taken the form of deflectable guidewires and deflectable stylets, typically operable from the proximal end of the lead or catheter, which controllably impart a curve to the distal portion of the catheter. One group of devices comprise deflectable stylets or guidewires which employ a straight, tubular outer member with a curved inner member, the inner and outer members movable relative to one another. Examples of this type of deflection mechanism are disclosed in U.S. Patent No. 4,136,703 issued to Wittkampf and U.S. Patent No. 5,728,148 issued to Bostrom et al.. Alternatively, deflection devices employing a curved outer member and a relatively straight inner member are also known to the art, as disclosed in U.S. Patent No. 4,676,249 issued to Arenas and U.S. Patent No. 5,040,543 issued to Badera et al. In devices of both types, the relative position of the inner member with respect to the outer member determines the degree to which the curved member (inner or outer) is allowed to display its preset curvature.

20 A more commonly employed approach to providing controllable deflection employs a generally straight outer member and a tension or push wire located within the outer member which on advancement or retraction causes the outer member to bend. Examples of such deflection mechanisms can be found in U.S. Patent No. 4,815,478 issued to Buchbinder et al., and U.S. Patent No. 4,940,062 issued to Hampton et al.

25 Particularly in the context of deflectable stylets intended for use in conjunction with implantable medical leads such as pacing and cardioversion leads, steerable stylets employing this third type of deflection mechanism are disclosed in U.S. Patent No. 5,662,119 issued to Brennan et al. , U.S. Patent No. 5,170,787 issued to

30

Lindegren, and U.S. Patent No. 5,327,906 issued to Fideler et al, all of which are incorporated herein by reference in their entireties.

While all of the mechanisms disclosed in the above cited prior art patents are at least to some degree workable, there is still a perceived need for a deflectable stylet or guidewire which is simple to manufacture and easy to use.

#### Background of the Invention

The present invention is directed toward providing a deflectable stylet or guidewire which is both simple to manufacture and readily operable using only one hand. The present invention accomplishes these goals by means of a deflection mechanism which employs a minimum of moving parts, and which is arranged to facilitate easy control of the degree of curvature displayed by the stylet or guidewire. More particularly, the present invention comprises a deflectable stylet or guidewire which is provided with a handle which has located at its distal end a rotatable and slidable knob or spinner surrounding the deflectable stylet or guidewire, provided with inwardly directed threading in conjunction with an inner slider member provided with outwardly directed threading, which may be advanced or retracted longitudinally within the handle by rotation of the knob or spinner but which is rotationally fixed with regard to the remainder of the handle assembly. An additional benefit of the inventive design is that the knob and the inner slider member together may be slid distally relative to the handle, providing a mechanism for more quickly forming a curve at in the stylet or guidewire. This feature is particularly beneficial when a curve is needed only temporarily, for example in conjunction with deflecting the tip of the stylet to facilitate entry into a desired blood vessel, such as the coronary sinus.

The steerable stylet or guidewire is provided with an outer tubular member and an inner tension wire, with the outer tubular member engaged at its proximal end with the inner slider member of the handle and the tension wire of the deflectable stylet or guidewire fixedly engaged with the remainder of the handle assembly. By means of this configuration, rotation of the knob or spinner produces advancement or retraction of the outer, tubular member of the deflectable stylet or guidewire relative to the handle assembly, which in turn causes the deflected stylet or guidewire to exhibit a

desired degree of curvature. Simply sliding the knob or spinner and the inner slider member distally together also serves to move the outer tubular member of the stylet relative to the tension wire, inducing a desired degree of curvature.

By means of the mechanism described above, a deflectable stylet is provided which conveniently allows for placement of the spinner or knob at the distal end of the handle where it may be readily grasped by the thumb and forefinger of the user, while the remainder of the handle may be grasped by the palm and the other three fingers of the user's hand. The design of the present invention requires only two moving parts within the handle assembly in order to provide for deflection of the distal tip of the guidewire or catheter, providing an assembly which is relatively inexpensive and simple to manufacture.

The distal portion of the handle is provided with a recess which allows for insertion of the connector assembly of an implantable electrical lead such as a pacemaker or defibrillator lead, allowing the connector assembly to be located in a fixed relationship with the inner, moveable slider member of the handle, while allowing the knob or spinner member to freely rotate around the connector assembly of the lead. The recess also inherently serves as a strain relief, preventing bending or kinking of the deflectable guidewire at the point it exits the slider.

#### Brief Description of the Drawings

Figure 1 is a plan view of a deflectable stylet according to the present invention.

Figure 2 is a plan view of the deflectable stylet of Figure 1 shown inserted into an implantable cardiac pacing lead.

Figure 3 is a sectional view through the handle portion of the deflectable stylet illustrated in Figure 1.

Figure 4 is a sectional view through an alternative embodiment of the handle portion of a deflectable stylet according to the present invention.

#### Detailed Description of the Preferred Embodiments

Figure 1 illustrates a plan view of a deflectable stylet according to the present invention. The deflectable stylet 16 is provided with a handle 10 provided with a main handle portion 12 and a spinner or knob portion 14, mounted rotatably with respect to the primary handle portion 12. The primary handle portion 12 is provided with circumferential grooving at its proximal end, while the spinner or knob 14 is may be provided with external ribbing or knurling as illustrated. The deflectable stylet 16 exits from a proximal recess 15, within spinner or knob 14. The rotation of spinner or knob 14 or distal advancement of knob 14 relative to the handle 12 causes deflection of the distal portion of stylet 16 to a curved configuration as illustrated at 16A.

Deflectable stylet 16 may take the form of any known deflectable stylet employing an outer tubular member and an inner tension wire which, when it applies tension to the distal tip of deflectable stylet 16, causes the tip of the stylet to curve. Appropriate designs for the deflectable stylet 16 include those described in the Brennen et al, Lindegren and Fideler patents discussed above and incorporated herein by reference in their entireties. Alternatively, deflectable stylet 16 may be replaced by a deflectable guidewire, for example, as disclosed in the above-cited Buchbinder patent, also incorporated herein by reference in its entirety. In all of these various guidewires and stylets, the basic structure of the deflectable stylet or guidewire consists of an outer tube which in a relaxed condition displays a generally straight configuration, and an internal tension wire coupled to the distal portion of the guidewire, and arranged such that upon application of tension to the distal tip of the guidewire or stylet, the distal portion of the guidewire or stylet exhibits a curved configuration.

Figure 2 is a plan view of the deflectable stylet of Figure 1 inserted into a cardiac pacing lead 20. Cardiac pacing lead 20 is provided with a connector assembly 18 located at its proximal end, which typically carries a connector pin as is typical of cardiac pacing leads. For example, the distal portion of the connector assembly 18 may correspond to the IS-1 connector standard as disclosed in U.S. Patent No. 4,922,607 issued to Doan et al., also incorporated herein by reference in its entirety. However, other connector configurations, such as disclosed in U.S. Patent No. 4,488,561 issued to Doring or U.S. Patent No. 4,572,605 issued to Hess et al., both



also incorporated herein by reference in their entireties, may also be employed. At the distal end of pacing lead 20 is located a fixed helical electrode 22, such as that disclosed in U.S. Patent No. 5,473,812 issued to Morris et al. and incorporated herein by reference in its entirety, which is screwed into heart tissue in order to stimulate the heart. However, any other type of known pacing electrode may be substituted for electrode 22, or alternatively other types of electrodes such as cardioversion or defibrillation electrodes may be added to or substituted for electrode 22. Examples of pacing and cardioversion electrodes generally that might be employed in conjunction with a lead to be deflected by the deflectable stylet of the present invention include those described in U.S. Patent No. 5,282,844 issued to Stokes et al., U.S. Patent No. 4,506,680 issued to Stokes, U.S. Patent No. 4,033,357 issued to Helland et al., U.S. Patent No. 4,727,877 issued to Kallok, U.S. Patent No. 5,115,818 issued to Holleman et al. and U.S. Patent No. 5,728,149 issued to Laske et al., all also incorporated herein by reference in their entireties.

As illustrated, the connector assembly 18 of the lead 20 is inserted into the distal facing opening 15 within spinner or knob 14. The spinner or knob 14 is free to rotate and slide with respect to connector assembly 18. The internal slider member (not visible in this view) located within handle 10 may either frictionally engage the connector pin of the connector assembly 18, or may be free to rotate with respect to the connector pin. For example, in the context of a device employing a fixed helical electrode, rotation of the entire lead with respect to the deflectable stylet would be required in order to screw the helical electrode 22 into heart tissue. However, in the context of a lead employing a tined electrode or employing other electrodes not requiring rotation of the lead body to accomplish fixation, the inner slider member of the handle 10 might frictionally engage the connector pin of connector assembly 18, further facilitating the steering of the lead through the vascular system to the desired location within the heart.

Figure 3 illustrates a sectional view through the handle 10 of the deflectable stylet illustrated in Figure 1. The handle comprises a main handle portion 12 and a spinner or knob portion 14, both of which may be molded plastic parts. Spinner 14 is provided with inwardly facing screw threads 38 which engage with correspondingly

outwardly facing screw threads 36 on the inner slider member 34. Fixedly coupled to the proximal end of slider 34 is a cylindrical extension 44 which is provided with two oppositely arranged outwardly projecting tabs 46 which engage with corresponding longitudinal grooves 48 formed in the major handle portion 12. Slider 34 and extension 44 may also be molded plastic parts. Interaction of the outwardly extending tabs 46 and the grooves 48 prevent rotation of tubular extension 44 and of slider member 34 relative to the major handle portion 12. As such, rotation of knob or spinner 14 relative to the major handle portion 12 causes proximal or distal movement of slider member 34 and extension 44 relative to both the major handle portion 12 and the knob or spinner 14.

The deflectable stylet 16 is arranged such that the outer tubular member 30, which be formed of stainless steel or nitinol tubing is fixedly mounted within the proximal portion 42 of the inner lumen 40 of slider 34, while the tension wire 32 extends through slider 34 to an anchoring mechanism which comprises a threaded rod 50 and an associated adjuster nut 52, located within the major handle portion 12. The threaded rod 50 is provided with a lumen through which tension wire 36 passes, and is arranged such that a ball 51 or other expanded diameter portion located at the proximal end of tension wire 32 anchors the wire with respect to threaded rod 50. Threaded rod 50 and nut 52 are both mounted rotationally fixed with respect to major handle portion 12, with adjuster nut 50 employed to position tension wire 32 so that in the circumstance in which the internal slider 34 is located at its most proximal position (as illustrated), no tension is applied to the distal tip of the outer tubular member 30 of the deflectable stylet 16, so that the deflectable stylet 16 displays a straight configuration. On rotation of spinner or knob 14 to advance inner slider member 34 with respect to the major handle portion 12, the outer tubular portion 30 of the deflectable stylet is also advanced with respect to tension wire 32, causing tension wire 32 to apply tension to the distal tip of the tubular member 30, correspondingly causing deflection of the tubular member.

Opening 15 in the distal portion of the knob or spinner 14 is sized to accept the connector assembly of the lead with which the deflectable stylet is intended to be used, with sufficient clearance, so that rotation of knob or spinner 14 does not cause

corresponding rotation of the connector assembly. The internal lumen 40 of the inner slider member 34 may be sized either to frictionally engage a connector pin at the proximal end of the lead connector assembly, or may be sized to be slightly greater than the connector pin of the associated lead. If the opening 40 is sized to be somewhat greater than the outer diameter of the connector pin, then the entire lead may be rotated with respect to the deflectable stylet. This is particularly desirable in the context of a lead as illustrated in Figure 1 which employs a fixation helix 22 (Fig. 2), fixedly mounted to the distal end of the lead body, as it allows the lead to be screwed into the tissue, around the stylet, in its deflected configuration. As noted above, however, as noted in the case of a lead employing a tined electrode or other fixation mechanism, it may be desirable to size the internal lumen 40 so that it frictionally engages a connector pin on the lead.

Figure 4 illustrates a cross-sectional view through an alternative embodiment of the handle portion of a deflectable stylet according to the present invention. The deflectable stylet 116 corresponds to deflectable stylet 16 illustrated in Figures 1 and 3 above, and includes an outer tubular member 130 which may take the form of a metal tube and an inner tension wire 132. Like the handle illustrated in Figure 3, the handle 110 illustrated in Figure 4 includes a spinner or knob portion 114 which is rotatably and slidably mounted relative to a major handle portion 112, which serves to advance or retract an inner slider portion 134, which is mechanically coupled to the outer tube 130 of deflectable stylet 116.

The proximal portion of the internal slider member 134 is provided with outwardly facing projections 146 which engage with a correspondingly shaped inner surface 148 of the major handle member 112 to prevent rotation of inner slider member 134 relative to handle 112. The proximal end of tension wire 132 is crimped, welded or otherwise coupled to a proximal tubular member 150 which may also be fabricated of hypo tubing and which is provided with a loop 154 at its proximal end. Tubular member 150 extends through the internal lumen through slider member 134, but is sized so that slider member 134 may be freely be moved proximally or distally with respect to the tubular member 150. Tubular member 150 is maintained in fixed longitudinal relationship with the major handle portion 112 by means of a pin 154

which passes through loop 152 and is anchored in end piece 156 of the handle 110. Located at the proximal end of the assembly is strain relief 133, which prevents undue stress at the point at which deflectable stylet 116 exits inner slider member 134. Operation of the device illustrated in Figure 4 corresponds to that of the device  
5 illustrated in Figure 3, with rotation or sliding of the knob or spinner 14 relative to the major handle portion 112 causing advancement of the outer tubular member 130 of deflectable stylet 116, correspondingly causing tension wire 132 to exert tension on the distal end of the outer tubular member 130 and causing it to assume a desired curved configuration.

10           While the above illustrated embodiments take the form of deflectable stylets, it should be understood that the present invention is equally applicable to deflectable guidewires as discussed above. Moreover, while it is believed that the most likely commercial embodiment of the present invention is a guidewire or stylet which is removably insertable into a catheter or lead body, the present invention may also have  
15 utility in the context of a deflection mechanism which is fabricated as a permanent part of a deflectable catheter, such as an electrophysiology mapping or ablation catheter, or other catheters of the type which typically include deflection mechanisms and handles permanently affixed to the catheters or lead bodies. As such, the above disclosed embodiments should be considered exemplary rather than limiting with  
20 regard to the scope of the claims that follow.

In conjunction with the above specification, I claim:

## CLAIMS:

1. Apparatus for deflecting a catheter or lead, comprising:  
an outer tubular member;  
5 a tension member mounted within the outer tubular member and coupled to the outer member;  
a handle comprising a major handle portion which has located at its distal end a rotatable knob, surrounding a proximal portion of the outer tubular member and provided with inwardly directed threading; and  
10 an inner slider member provided with outwardly directed threading engaging the inwardly directed threading of the knob, which slider is advanced or retracted longitudinally within the handle by rotation of the knob but which is rotationally fixed with regard to the major handle portion; wherein  
the outer tubular member is engaged at its proximal end with the inner slider  
15 member and the tension wire is fixedly engaged with the major handle portion, whereby rotation of the knob results in advancement or retraction of the outer tubular member relative to the tension wire and the major portion of the handle, which in turn causes the deflection of the outer tubular member.
- 20 2. An apparatus according to claim 1, wherein the knob is slidable longitudinally relative to the major handle portion whereby deflection of the outer tubular member may also be accomplished by sliding the knob longitudinally.
3. An apparatus according to claim 1 or claim 2 wherein the outer tubular  
25 member is a metal tube.
4. An apparatus according to claim 1 or claim 2 wherein the tension wire member is a metal wire.

5. An apparatus according to claim 1 or claim 2 wherein the knob is provided with a distal facing recess surrounding a proximal portion of the outer tubular member.




Fig. 1






Fig. 2







# INTERNATIONAL SEARCH REPORT

Internatio Application No

PCT/US 99/08409

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 A61M25/01

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M A61B A61N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 91 01772 A (RADI MEDICAL SYSTEMS) 21 February 1991 (1991-02-21) page 4, paragraph 3 - page 6, paragraph 2; figures 4-10 ---	1,2
A	US 4 757 827 A (ROUCHER LEO ET AL) 19 July 1988 (1988-07-19) cited in the application column 4, line 29 - column 5, line 27; figures ---	1,3-5
A	US 5 327 906 A (FIDELER BRIAN L) 12 July 1994 (1994-07-12) cited in the application column 2, line 28 - column 3, line 19; figures --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 August 1999

Date of mailing of the international search report

26/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kousouretas, I

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/08409

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 5 662 606 A (TAIMISTO MIRIAM H ET AL)</p> <p>2 September 1997 (1997-09-02)</p> <p>column 8, line 15 - column 9, line 3</p> <p>-----</p>	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US 99/08409

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9101772 A	21-02-1991	AU 6067390 A	11-03-1991
		SE 8902630 A	01-02-1991
		SE 468306 B	14-12-1992
		SE 9003758 A	01-02-1991
US 4757827 A	19-07-1988	AT 122551 T	15-06-1995
		AU 603887 B	29-11-1990
		AU 1485488 A	14-09-1988
		AU 6190790 A	20-12-1990
		AU 6190890 A	20-12-1990
		CA 1301004 A	19-05-1992
		DE 3853798 D	22-06-1995
		DE 3853798 T	23-11-1995
		EP 0303680 A	22-02-1989
		JP 1502881 T	05-10-1989
		WO 8806020 A	25-08-1988
		US 4813434 A	21-03-1989
		US 4815478 A	28-03-1989
US 5327906 A	12-07-1994	NONE	
US 5662606 A	02-09-1997	US 5364352 A	15-11-1994
		US 5857997 A	12-01-1999
		CA 2118725 A	13-09-1994
		EP 0616794 A	28-09-1994
		EP 0898940 A	03-03-1999
		JP 7088093 A	04-04-1995